

# Grader blade with booms LSB

The grader blade can be used for land recovery by collecting larger stones. It is possible to request a version with closer tines, that allow to retain smaller stones.



## Technical data sheet

|                                |  | A10   |       |       |       |       |       | A20   |       |        |        | A30    |        |        |
|--------------------------------|--|-------|-------|-------|-------|-------|-------|-------|-------|--------|--------|--------|--------|--------|
| Wheel track (A)                |  | 800   | 1000  | 1100  | 1200  | 1300  | 1400  | 1500  | 1600  | 1300   | 1400   | 1500   | 1600   | 1700   |
| Mouldboard width (B)           |  | 1900  | 1900  | 2020  | 2020  | 2160  | 2140  | 2300  | 2300  | 2300   | 2300   | 2560   | 2560   | 2560   |
| Mouldboard height (C)          |  | 550   | 550   | 550   | 550   | 550   | 550   | 550   | 550   | 650    | 650    | 650    | 650    | 650    |
| Max height from the ground (D) |  | 700   | 700   | 700   | 700   | 700   | 700   | 700   | 700   | 800    | 800    | 800    | 800    | 800    |
| Excavation height (E)          |  | 250   | 250   | 250   | 250   | 250   | 250   | 250   | 250   | 300    | 300    | 300    | 300    | 300    |
| Tractor power                  |  | 44-55 | 44-55 | 44-55 | 44-55 | 44-55 | 44-55 | 44-55 | 44-55 | 60-110 | 60-110 | 60-110 | 60-110 | 60-110 |
| Tractor power                  |  | 32-41 | 32-41 | 32-41 | 32-41 | 32-41 | 32-41 | 32-41 | 32-41 | 44-81  | 44-81  | 44-81  | 44-81  | 44-81  |

*N.B. Technical data and images are indicative and not binding, as they may also vary depending on the type of tractor equipped*